

Branson 15 Series



Everything you'd desire for your perfect compact tractor
[including a very affordable price]



Spacious Ergonomically
Designed Operator's
Platform with a Deluxe
Adjustable Seat

Cruise Control on
HST Models

3-Range
Transmission

Customized BL150 Front End
Loader with a 2701 lbs.
Lift Capacity

Dual
Hydraulic
Pumps

"Hydro-MAX" HST Transmission
with Auto Throttle
or Synchro-Shuttle Transmission

If you could start from scratch to design your ideal tractor, the **Branson 15 Series tractors** would probably come pretty close to that perfect tractor. Each design element has been carefully considered to give you a smooth and comfortable ride, combined with easy maintenance, a great warranty plan — and best of all, an affordable price. What more could you want in a perfect compact tractor? With six models, you can choose the horsepower, transmission, tires and implements that best suits your work. Branson 15 Series compact tractors are also available in CAB models.



2020 DEALER'S CHOICE AWARD

Branson 15 Series Compact Tractors - R and h

	2515R	2515h	3015R	3015h	3515R	3515h	4215R	4215h	4815R	4815h
ENGINE										
Model	A1700N6	A1700N6	A1700N3	A1700N3	A1700N2	A1700N2	A2000N2	A2000N2	A2300N2	A2300N2
Type	Vertical, 4 Cycle, Water Cooled, Diesel, EPA Tier 4 Certified									
Combustion System	Swirl Chamber									
Aspiration	Naturally									
Engine HP	24	25	30	30	35	35	42	42	48	48
PTO HP	21	21	25	25	30	30	36	36	40	40
Engine / RPM	2100		2600							
No. of Cylinders	3						4			
Displacement / cu. in.	104.5						139.5			
Type of Air Cleaner	Dry Element									
Fuel Tank Capacity / gal	7.1									
TRANSMISSION										
Main Shift	Synchromesh	HST	Synchromesh	HST	Synchromesh	HST	Synchromesh	HST	Synchromesh	HST
Forward / Reverse Method	Synchromesh Shuttle	-	Synchromesh Shuttle	-	Synchromesh Shuttle	-	Synchromesh Shuttle	-	Synchromesh Shuttle	-
No. of Traveling Speeds	12F / 12R	3 Range	12F / 12R	3 Range	12F / 12R	3 Range	12F / 12R	3 Range	12F / 12R	3 Range
Traveling Speeds (F / R) mph	12/11.6	15.2/15.2	14.9/14.3	18.7/18.7	14.9/14.3	18.7/18.7	14.9/14.3	18.7/18.7	14.9/14.3	18.7/18.7
HYDRAULIC SYSTEM										
Lift Control Type	Position Control									
3-Point Hitch	Category 1									
Lift Capacity / lbs.	3306									
PTO										
Type	Independent PTO (6 Spline Shaft)									
Speed / RPM	533 / 791 (2600)									
Power (PTO) @ 2,600 rpm / HP	21	21	25	25	30	30	36	36	40	40
DIMENSIONS										
Overall Length / in.	120.9									
Overall Width / in.	56.3									
Overall Height / in.	97.3									
Wheelbase / in.	65.7									
Ground Clearance / in.	14.4									
Weight / lbs.	2989	2969	3183	3163	3183	3163	3278	3258	3278	3258
TIRES										
Agricultural Tires (AG 10)	Front Tires - 7 -16 / Rear Tires - 12.4 - 24									
Industrial Tires (IND 10)	Front Tires -28 x 8.50 x 15 / Rear Tires - 43 x 16.00 - 20									

Learn more at our website - bransontractor.com

Design, materials and/or specifications are subject to change without notice and without liability therefore. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas. Contact your local Branson dealer for more information.



Branson Machinery LLC, 2100 Cedartown Highway, Rome, Georgia 30161

Printed in the USA • January 2021