T574

Compact, Series 4
55 hp

TYM TRACTORS

Packed with features to help accomplish your goals

Take on tough jobs in tight spaces with the T574. This tractor brings you the best features from our compact and utility ranges, balancing high power output with maximized maneuverability.

1. Cruise control switch

2. Projection headlights

3. 4-port rear hydraulic valve

4. 3-range hydrostatic transmission

5. PTO switch

6. Digital instrument panel



Telescopic linkages and stabilizers

Telescopic linkages allow implements to be easily connection and swapped out, without needing input from the operator cabin. Stabilizers make it possible for the tractor to adapt to implements of varying loads, without putting too much pressure on the engine productivity.



4-cyclinder Kukje diesel engine with high output

Equipped with a powerful, Tier-4 certified 4-cylinder engine, this tractor has an output comparable to utility tractors while maintaining the dimensions of a sub-compact tractor. The durable body and efficient engine come together to perform medium duty applications efficiently and productively.

Superior operator amenities for greater productivity

Fully equipped with modern amenities to maximize operator comfort, this tractor is complete with a large cup holder, wireless smartphone charging dock, multiple USB ports to charge personal devices and a bluetooth speaker. These features are designed to promote productivity, keeping drivers hydrated, connected and alert during every job.



Durable power steering and axle configuration

The heavy duty 4WD front axle allows the tractor to lift heavy loads and tow large implements. Powerful hydraulics support the power steering system, which benefits from a dual action mechanism using a hydraulic cylinder and tandem type hydraulic pump.

Add-on work lights, wipers, mirrors and alerts as a standard

An additional rear view mirror and work lights and vipers for the front and rear of the tractor facilitate safer operations, particularly in low visibility conditions like rain or dust storms. A digital display indicates tractor performance and engine vitals, which is critical for nighttime operations.

3rd function hydraulic valve to enhance implement capabilities

Allowing for versatile implement handling, this tractor comes with ready with a 3rd function installation kit. It can maximize the use of a bucket implement with 4-in-1 functionality, including lifting, tilting, dumping and grappling.

Technical specifications

ENGINE	
Engine manufacturer	Kukje A2300T3
Type	Turbo
Gross engine power	55 hp
PTO power	44.7 hp | 32.9 kW
Rated engine speed	2600 rpm
No. of cylinders	4
Displacement	139.5 cu. in. | 2286 cc
Air cleaner	Dual Dry
Alternator	12V, 70A
Fuel system	IDI
HYDRAULIC SYSTEM	
Pump type	Dual Gear Pump
Implement flow	7.66 gpm | 29 l/min
Steering flow	4.25 gpm | 16.09 l/min
Total flow	11.91 gpm | 45.08 l/min
Category, 3-point hitch	I
Hitch lift capacity	3822 lb | 1733 kg
Hitch lift capacity at 24 inches behind link ends	3057 lb | 1387 kg
Lift control type	Position/Draft
No. of standard remote valves	2
STANDARD TIRES	
R1 Agricultural - Front	Farm Specialist 9.5-16 NHS TL 6PR
R1 Agricultural - Rear	Farm Specialist 14.9-24 NHS TL 6PR
R3 Turf - Front	Multi-Trac CS 27x10.50-15 NHS TL 4PR
R3 Turf - Rear	Multi-Trac CS 44x18.00-20 NHS TL 4PR
R4 Industrial - Front	Trac Chief 12-16.5 NHS TL 6PR
R4 Industrial - Rear	Xtra Grip 16.9-24 NHS TL 6PR

POWERTRAIN	
Transmission type	Sync Shuttle
No. of speeds	F8xR8
Max. traveling speed	18.45 mph | 29.7 kmph
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Dry Single Plate
Max. traveling speed_M	16 mph | 25.8 kmph
Max. traveling speed_HST	15.1 mph | 24.3 kmph
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	141.3 in. | 3590 mm
Overall width	63.8 in. | 1620 mm
Wheelbase	76.2 in. | 1935 mm
Height to top of ROPS	102.1 in. | 2594 mm
Min. ground clearance	13.8 in. | 350 mm
Min. turn radius with brakes	121.2 in. | 3080 mm
Min. turn radius without brakes	131.5 in. | 3340 mm
Weight with ROPS	3887 lb | 1763 kg
Weight with cab	4233 lb | 1920 kg
CAPACITIES	
Fuel tank	17.0 gal | 60 L
Coolant	6.9 qt | 6.53 L
Crankcase	6.8 qt | 6.4 L
Transmission/Hydraulics system	9.2 gal | 34.8 L
Front axle	10.5 qt | 9.9 L
PTO	
PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540 rpm

T574

Compact, Series 4
55 hp

TX57 Front-End Loader

Attachments

The TX57 front-end loader takes advantage of the power and durability of TYM compact tractors. Ideal for tasks that require more strength, the TX57 front-end loader can help you get your tasks done more efficiently.

Lift height	109.4 in. / 2780 mm
Lift capacity	2790 lb / 1266 kgf
Bucket capacity	11.3 cu. ft / 0.32 cu. m

CAPACITIES & REACH	
Lift height	109.4 in. | 2780 mm
Max. lift height under level bucket	101 in. | 2566 mm
Clearance with bucket dumped	83.6 in. | 2123 mm
Reach at maximum lift height	17.6 in. | 447 mm
Max. dump angle	50°
Reach with bucket on ground	71.5 in. | 1815 mm
Max. rollback angle	35°
Digging depth	5.5 in. | 140 mm
Lift capacity	2790 lb | 1266 kgf
Breakout force at ground level, pivot pins	5316 lb | 2411 kgf
Bucket rollback force at ground line	4356 lb | 1976 kgf
Bucket capacity	11.3 cu. ft | 0.32 cu. m
Self leveling	NA
Relief valve setting (Loader contol valve)	2489 psi | 175 kg/sq. cm

DIMENSIONS & WEIGHTS	
Overall height in carry position	56.8 in. | 1442 mm
Depth of Attachment (to the back of the inner shell)	21.1 in. | 537 mm
Height of Attachment	20.4 in. | 519 mm
Length of Attachment (to pivot pin)	27.3 in. | 694 mm
Weight of boom & quick attach mechanism (1)	535.7 lb | 243 kg
Weight of mounting frame (2)	313 lb | 142 kg
Weight of bucket (3)	271.2 lb | 123 kg
Loader total weight (1+2+3)	1120 lb | 508 kg
Lift cylinder	2.4x1.4 in. | 60x35 mm
Bucket cylinder	2.4x1.4 in. | 60x35 mm
Attachment used for specification	72 in. | 1830 mm
CYCLE TIMES	
Boom raising time	6.4 sec
Boom lowering time	4.2 sec
Bucket rollback time	3.8 sec
Bucket dumping time	5.7 sec

COMPATIBLE BUCKET SIZES

TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.

72" Front-End Loader bucket

BY85 Backhoe

Attachments

For heavy duty tasks, you can depend on TYM BY85 to deliver performance and power. Built to take advantage of the features of TYM Series 4 compact tractors, the TYM BY85 backhoe attachment is ideal for applications that require the extra power.

Digging depth	103.2 in. / 2621 mm
Loading height	92.4 in. / 2347 mm
Backhoe reach	134.4 in. / 3414 mm

CAPACITIES & REACH	
Backhoe reach	134.4 in. | 3414 mm
Swing angle	180°
Bucket rotation	151°
Stabilizer spread (lowered position)	88.8 in. | 2256 mm
Stabilizer spread (raised position)	68.4 in. | 1737 mm
PERFORMANCE	
Digging depth	103.2 in. | 2621 mm
Loading height	92.4 in. | 2347 mm
Max. leveling angle	10°
Angle of departure	21°

DIMENSIONS & WEIGHTS	
Transport overhang	50.4 in. | 1280 mm
Transport height (max.)	91.2 in. | 2317 mm

COMPATIBLE BUCKET SIZES

TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.

9" backhoe bucket	12" backhoe bucket
16" backhoe bucket	18" backhoe bucket
24" backhoe bucket	36" backhoe bucket

Upgrades for the Series 4, T574

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories

Block heater
Mid-PTO kit
T85A Mechanical Thumb
Front counterweights
BHPAD200 Street Pads

Options

Tire	R1 Agricultural Tires	F Farm Specialist 9.5 - 16 NHS TL 6PR	R Farm Specialist 14.9-24 NHS TL 6PR
Tire	R3 Turf Tires	F Multi - Trac CS 27x10.50	R Multi-Trac CS 44x18.00-20 NHS TL 4PR
Tire	R4 Industrial Tires	F Trac Chief 12 - 16.5 NHS TL 6PR	R Xtra Grip 16.9-24 NHS TL 6PR

TYM
TRACTORS

Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world