3620

Compact, Series 3
35 hp

A high-performance compact tractor built to take on challenges of all sizes

Superior performance meets high efficiency in this customizable Series 3 tractor. The 3620 can be configured as you see fit to drive productivity and it's equipped with the features designed to maintain your comfort throughout tasks of varying intensities.

1. Hood design

3. Ergonomic lever

5. High-capacity fuel tank

2. Comfortable suspension seat

4. Rear work light

6. Joystick control for front-end loader



Eco-friendly TYM Tier 4 engine

Equipped with a naturally aspirated engine designed and manufactured by TYM, the tractor is designed to be eco-friendly and fuel-efficient without compromising on performance.

Tilt steering wheel

The tilt steering wheel allows operators to adjust the position of the steering wheel for a more comfortable driving experience.

PTO on/off switch

Safety is a top priority. The PTO switch ensures secure operation of all tractor attachments.

Differential lock system and low turning angle

The differential lock system, activated with easily accessible levers, provides enhanced traction in slippery work environments, while a 52˚ turning angle makes operation in narrow areas much easier.



Water-separating fuel filter

The water-separating fuel filter prevents foreign substances from entering the fuel, ensuring better engine starting performance and preventing damage to the machine.



Optional tires for various working conditions

In addition to standard agricultural tires, industrial and turf tires are also available for versatile working conditions.

Technical specifications

ENGINE	
Engine manufacturer	TYM T1700N2
Type	Natural aspiration
Gross engine power	35 hp | 26.0 kW
PTO power	28 hp | 20.8 kW
Rated engine speed	2500 rpm
No. of cylinders	3
Displacement	104.5 cu. in. | 1714 cc
Air cleaner	Dry element
Alternator	12V, 50A
Fuel system	IDI
POWERTRAIN	
Transmission type	3620R: Synchromesh 3620H: HST
No. of speeds	3620R: F16 x R16 3620H: 4-Range
Max. traveling speed	3620R: 16 mph | 25.7 km/h 3620H: 19.5 mph | 31.4 km/h
Brakes	Wet, Multi disc
Steering	Hydrostatic
Clutch	Dry single type | No
CAPACITIES	
Fuel tank	11.8 gal | 45 L
Coolant	6 qt | 5.7 L
Crankcase	4.5 qt | 4.3 L
Transmission/Hydraulics system	3620R: 10.3 gal | 39 L 3620H: 11.1 gal | 42 L
Front axle	6.8 qt | 6.4 L

PTO	
PTO type	Independent
PTO control	Wet/Multi disc
PTO rear	540/750 rpm
HYDRAULIC SYSTEM	
Pump type	Dual gear pump
Implement flow	7.7 gpm | 29.3 L/min
Steering flow	4.2 gpm | 15.8 L/min
Total flow	11.9 gpm | 45.1 L/min
Category, 3-point hitch	I
Hitch lift capacity	1500 lb | 3306 kg
Hitch lift capacity at 24 inches behind link ends	2425 lb | 1100 kg
Lift control type	Position
No. of standard remote valves	Optional (up to 4)
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	127.4 in. | 3236 mm
Overall width	64.9 in. | 1650 mm
Wheelbase	71.1 in. | 1806 mm
Height to top of ROPS	98.4 in. | 1200 mm
Height to top of cabin	-
Min. ground clearance	15.5 in. | 394 mm
Min. turn radius with brakes	(L) 97.2 in. | 2740 mm / (R) 105.1 in. | 2670 mm
Min. turn radius without brakes	(L) 128.7 in. | 3270 mm / (R) 126.0 in. | 3200 mm
Weight with ROPS	3754 lb | 1703 kg
Weight with cab	-
STANDARD TIRES	
R1 Agricultural - Front	9.5-16
R1 Agricultural - Rear	12.4-28
R3 Turf - Front	1: 27x8.5-15 2: 29x12.5-15
R3 Turf - Rear	1: 41x14-20 2: 44x18-20
R4 Industrial - Front	10x16.5
R4 Industrial - Rear	420/70x24

BH200 Backhoe

Attachments

The BH200 complements the power and strength of the Series 3 compact tractors, enhancing performance and versatility without compromising safety.

Digging depth	91.2 in. | 2317 mm
Loading height	90 in. | 2286 mm
Backhoe reach	123.6 in. | 3140 mm

PERFORMANCE	
Digging depth	91.2 in. | 2317 mm
Loading height	90 in. | 2286 mm
Max. leveling angle	10°
Angle of departure	21°
CAPACITIES & REACH	
Backhoe reach	123.6 in. | 3140 mm
Swing angle	180°
Bucket rotation	149°
Stabilizer spread (lowered position)	88.8 in. | 2256 mm
Stabilizer spread (raised position)	68.4 in. | 1737 mm
DIMENSIONS & WEIGHTS	
Transport overhang	46.8 in. (1189 mm)
Transport height (max.)	85.2 in. | 2164 mm

Compatible bucket sizes	9" backhoe bucket
Compatible bucket sizes	12" backhoe bucket
Compatible bucket sizes	16" backhoe bucket
Compatible bucket sizes	18" backhoe bucket
Compatible bucket sizes	24” backhoe bucket

COMPATIBLE BUCKET SIZES

TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.

Large_09	Large_12
Large_16	Large_18
Large_24	

BL200 Front-End Loader

Attachments

The BL200 front-end loader takes advantage of the power and durability of TYM compact tractors. Ideal for tasks that require more strength, this front-end loader can help you get your tasks done more efficiently.

Lift height	106.6 in. | 2709 mm
Lift capacity at pivot point (max. height)	2701 lb | 1225 kgf
Bucket capacity	9.5 cu. ft | 0.27 cu. m

CAPACITIES & REACH	
Lift height	106.6 in. | 2709 mm
Max. lift height under level bucket	98.1 in. | 2491 mm
Clearance with bucket dumped	78.2 in. | 1987 mm
Reach at maximum lift height	14.6 in. | 371 mm
Max. dump angle	58°
Reach with bucket on ground	69.2 in. | 1758 mm
Max. rollback angle	35°
Digging depth	3.1 in. | 78 mm
Lift capacity at pivot point (max. height)	2701 lb | 1225 kgf
Breakout force at ground level, pivot pins	3660 lb | 1660 kgf
Bucket rollback force at ground line	2844 lb | 1290 kgf
Bucket capacity	9.5 cu. ft | 0.27 cu. m
Self leveling	NA
Relief valve setting (loader control valve)	2532 psi | 178 kg/sq. cm
Compatible bucket sizes	66" Front-end loader bucket
DIMENSIONS & WEIGHTS	
Overall height in carry position	50.9 in. | 1293 mm
Depth of Attachment (to the back of the inner shell)	20.9 in. | 530 mm
Height of Attachment	20.9 in. | 530 mm
Length of Attachment (to pivot pin)	28.2 in. | 716 mm
Weight of boom & quick attach mechanism (1)	521 lb | 236 kg
Weight of mounting frame (2)	284 lb | 129 kg
Weight of bucket (3)	269 lb | 122 kg
Loader total weight (1+2+3)	1075 lb | 487 kg
Lift cylinder	2.2 × 1.2 in. | 55 × 30 mm
Bucket cylinder	2.0 × 1.2 in. | 55 × 30 mm
Attachment used for specification	72 in. | 1830 mm
CYCLE TIMES	
Boom raising time	4.3 sec
Boom lowering time	2.8 sec
Bucket rollback time	2.9 sec
Bucket dumping time	4.2 sec

Upgrades for the Series 3, 3620

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories

Options

Tire	R3 Turf Tires	F 27x8.5 - 15	R 41x14-20
Tire	R3 Turf Tires	F 29x12.5 - 15	R 44x18-20
Tire	R1 Agricultural Tires	F 9.5 - 16	R 12.4-28
Tire	R4 Industrial Tires	F 10x16.5	R 420/70×24

Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world